

# XS Series

Single MPPT, Single Phase



Technical Data	GW700-XS	GW1000-XS	GW1500-XS	GW2000-XS	GW2500-XS	GW3000-XS	GW2500N-XS	GW3000N-XS
<b>PV String Input Data</b>								
Max.Input Power (W)	910	1300	1950	2600	3250	3900	3250	3900
Max. DC Input Voltage (V)	500	500	500	500	500	500	600	600
MPPT Range (V)	40~450	40~450	50~450	50~450	50~450	50~450	50~550	50~550
Start-up Voltage (V)	40	40	50	50	50	50	50	50
Nominal Input Voltage (V)	360	360	360	360	360	360	360	360
Max. Input Current per MPPT (A)	12.5	12.5	12.5	12.5	12.5	12.5	13	13
Max. Short Current per MPPT (A)	15.6	15.6	15.6	15.6	15.6	15.6	16.3	16.3
No. of MPP Trackers	1	1	1	1	1	1	1	1
No. of Input Strings per MPPT	1	1	1	1	1	1	1	1
<b>AC Output Data</b>								
Nominal Output Power (W)	700	1000	1500	2000	2500	3000	2500	3000
Nominal Output Apparent Power (VA)	700	1000	1500	2000	2500	3000	2500	3000
Max. Output Apparent Power (VA)	800*1	1100*1	1650*1	2200*1	2750*1	3300*1	2750*1	3300*1
Nominal Output Voltage (V)	230	230	230	230	230	230	220 / 230	220 / 230
Nominal Output Frequency (Hz)	50 / 60	50 / 60	50 / 60	50 / 60	50 / 60	50 / 60	50 / 60	50 / 60
Max. Output Current (A)	3.5	4.8	7.2	9.6	12	14.3	12	14.3
Nominal Output Current (A)	3	4.3	6.5	8.7	10.9	13	11.4 / 10.9	13.6 / 13
Output Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)							
Max. Total Harmonic Distortion	<3%	<3%	<3%	<3%	<3%	<3%	<3%	<3%
<b>Efficiency</b>								
Max. Efficiency	97.2%	97.2%	97.3%	97.5%	97.6%	97.6%	97.6%	97.6%
European Efficiency	96.0%	96.4%	96.6%	97.0%	97.2%	97.2%	97.2%	97.2%
<b>Protection</b>								
DC Insulation Resistance Detection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Residual Current Monitoring Unit	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
DC Reverse Polarity Protection	NA	NA	NA	NA	NA	NA	NA	NA
Anti-islanding Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
AC Overcurrent Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
AC Short Circuit Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
AC Overvoltage Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
DC Switch	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
DC Surge Arrester	Type III	Type III	Type III	Type III	Type III	Type III	Type III (Type II Optional)	
AC Surge Arrester	Type III	Type III	Type III	Type III	Type III	Type III	Type III	Type III
DC Arc Fault Circuit Interrupter	NA	NA	NA	NA	NA	NA	Optional	Optional
<b>General Data</b>								
Operating Temperature Range (°C)	-25~60	-25~60	-25~60	-25~60	-25~60	-25~60	-25~60	-25~60
Relative Humidity	0~100%	0~100%	0~100%	0~100%	0~100%	0~100%	0~100%	0~100%
Operating Altitude (m)	≤4000	≤4000	≤4000	≤4000	≤4000	≤4000	≤4000	≤4000
Cooling Method	Natural Convection							
Display	LED, LCD / Wi-Fi+APP / Bluetooth+APP							
Communication	Wi-Fi / LAN / RS485						RS485 / Wi-Fi	
Weight (Kg)	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
Size (Width × Height × Depth mm)	295 × 230 × 113							
Topology	Transformerless							
Night Power Consumption (W)	<1	<1	<1	<1	<1	<1	<1	<1
Ingress Protection Rating	IP65	IP65	IP65	IP65	IP65	IP65	IP65	IP65
DC Connector	MC4 (2.5~4mm <sup>2</sup> )							
AC Connector	plug and play connector							

\*1: For Belgium Max. Output Apparent Power (VA): GW700-XS is 700; GW1000-XS is 1000; GW1500-XS is 1500; GW2000-XS is 2000; GW2500-XS or GW2500N-XS is 2500; GW3000-XS or GW3000N-XS is 3000.

\*2: Only compatible with 2.4Ghz network.

\*: Please visit GoodWe website for the latest certificates.